# **Technical data sheet** Pressure clip for 8 cables

## Item number: 2204020





The metal pressure clip is halogen and fire load-free, and maintains a good mechanical stability even in fires. The pressure clip is also approved as a cable-specific variant for the maintenance of electrical functionality to DIN 4102 Part 12. The spacer 2033 D 15 x 3 G (must be ordered separately) increases the clamping height of pressure clips from 10 to 13 mm. The pressure clips are suitable for fireproof mounting above suspended fire protection ceilings in accordance with DIN 4102.



## Master data

Item number2204020Type2035 M A2Description 1Pressure clipManufacturerOBODimension8xNYM3x1,5MaterialStainless steelSurfaceBright, treatedSurface standard20Unit of quantityPiece		
Description 1 Pressure clip   Manufacturer OBO   Dimension 8xNYM3x1,5   Material Stainless steel   Surface Bright, treated   Surface standard 20	Item number	2204020
Manufacturer OBO   Dimension 8xNYM3x1,5   Material Stainless steel   Surface Bright, treated   Surface standard 20	Туре	2035 M A2
Dimension 8xNYM3x1,5   Material Stainless steel   Surface Bright, treated   Surface standard 20	Description 1	Pressure clip
Material Stainless steel   Surface Bright, treated   Surface standard 20	Manufacturer	OBO
Surface Bright, treated   Surface standard 20	Dimension	8xNYM3x1,5
Surface standard 20	Material	Stainless steel
Smallest sales unit 20	Surface	Bright, treated
	Surface standard	
Unit of quantity Piece	Smallest sales unit	20
	Unit of quantity	Piece
Weight 1.03 kg	Weight	1.03 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

### **Technical data**

No. of conductors NYM 3 x 1.5	8
Flame-resistant version	no
Maintain electrical functions	yes
Halogen-free	yes
With anchor	no