### **Technical data sheet**Trunking socket BRK, triple

**Item number: 6121032** 



Triple Signa In trunking socket with increased touch protection, incl. panel (a maximum of 3 Signa In units can be connected through plug combinations) 16 A/  $250 \text{ V}^{-}$ .



### 

Manufacturer OBO
Dimension 206x82x71
Colour Pure white; RAL 9010
Smallest sales unit 1
Unit of quantity Piece
Weight 30.3 kg
Weight unit kg/100 pc.

## **Technical data sheet**Trunking socket BRK, triple





# Dimensions 204

| Width  | 206 mm |
|--------|--------|
| Height | 82 mm  |

### Technical data

| Cover  | Complete housing             |
|--|------------------------------|
| Closable   | no                           |
| Connection type                                  | Screwless terminal           |
| Number of units                                  | 3                            |
| Number of modules (for modular construction)     | 3                            |
| Printed label/coding                             | Without printing             |
| Surface version                                  | Matt                         |
| Version for                                      | SCHUKO                       |
| Ejection mechanism                               | no                           |
| Fastening type                                   | Miscellaneous                |
| Labelling panel                                  | no                           |
| Error current protection                         | no                           |
| For more difficult conditions (according to VDE) | no                           |
| Halogen-free                                     | yes                          |
| Insulated installation                           | yes                          |
| Hinged cover                                     | no                           |
| Coding   | no                           |
| With on/off switch                               | no                           |
| With fine-wire fuse                              | no                           |
| With functional lighting                         | no                           |
| With orientation lighting                        | no                           |
| Mounting type                                    | Device installation duct     |
| Nominal voltage                                  | 250 V                        |
| Nominal current                                  | 16 A                         |
| Protection rating                                | IP20                         |
| Special power supply                             | Without special power supply |
| Socket angle                                     | 0°                           |
| Transparent                                      | no                           |
| Rotated central insert                           | no                           |
| Surge protection                                 | no                           |
|  |                              |