Technical data sheet

PYROCOMB® Intube pipe shell, Ø 90 mm

Item number: 7204296





Internally coated pipe shells with click lock. The inner space can be fitted with cables and electrical installation pipes completely. For interior application. CE-labelled, European approved construction product according to ETA-13/0904 and German general type approval. Fire resistance up to 120 minutes.

Closing with 2 foam plugs included in the delivery. The surface seal is created with $\mbox{PYROCOAT}\mbox{\sc B}$ ASX coating.

In some applications, the use of metallic tightening straps is prescribed to secure the pipe shells in light-duty partitions. Details can be found in the mounting instructions/approval.



Master data

7204296
CTS 09300
Pipe shell
internally coated
OBO
81x300mm
Grey
Polyvinylchloride
1
Piece
54 kg
kg/100 pc.


Technical data sheet

PYROCOMB® Intube pipe shell, Ø 90 mm

Item number: 7204296



Dimensions						
Ĩ	Î.		Length	300 mm		
	1		Dimension B	90 mm		
			Dimension d min.	80.6 mm		
			Dimension L	300 mm		
÷.		0				
1	1	O O				
1	1	(m				



Technical data

Fire protection version	Assembly insulation
Shape	Round
For opening, max.	100 mm
For opening, min.	100 mm
Accessories required	no