Technical data sheet

PYROPLUG® Shell drill crown insulation

Item number: 7202628





Pipe shell for cable insulation.

Consisting of a one-part, hard pipe sleeve and two soft plugs of 50 mm diameter. Protect the pipe sleeves and plugs against water in order to guarantee safe fo-

aming in case of fire. For interior application.

FBA-D pipe shells, FBA-DS plug, FBA-M fire protection compound, FBA-D-BS additional kit, wall plate







Permanently elastic, closed-pore foam

Master data


Item number	7202628
Type	FBA-D150
Description 1	Drill crown insulation
Manufacturer	OBO
Dimension	Ø78x150mm
Colour	Red
Material	Permanently elastic, closed-pore foam
Smallest sales unit	1
Unit of quantity	Piece
Weight	19.2 kg
Weight unit	kg/100 pc.

Technical data sheet PYROPLUG® Shell drill crown insulation



Item number: 7202628

Dimensions				
	<u> </u>	Length	150 mm	
i i l		Width	78 mm	
î î	0	Dimension L	150 mm	
1 !	150		·	
	~			
1 1				
: : : I	7			



Te		

Fire protection version	Box body
Shape	Round
For opening, max.	100 mm
For opening, min.	78 mm
Accessories required	ves