Technical data sheet

Device installation trunking, desk trunking







GEK-S device installation trunking suitable for installation on desks, etc. The visible surfaces of the painted GEK-S device installation trunking are laminated. The trunking system possesses self-contacting locking straps to accept a sheet steel partition. The equipotential bonding between the trunking bases takes place using the coupling. The protective measure and the equipotential bonding is guaranteed between the cover and the base by the self-contacting trunking cover. The actual system opening is 76.5 mm. The cover must be ordered separately.



St

Steel

Master data

Item number 6282700 Type GEK-SA133110RW Description 1 Device installation trunking Description 2 asymmetrical Manufacturer OBO Dimension 133x110x2000 Colour Pure white; RAL 9010 Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg Weight unit kg/100 m		
Description 1 Device installation trunking Description 2 asymmetrical Manufacturer OBO Dimension 133x110x2000 Colour Pure white; RAL 9010 Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Item number	6282700
Description 2 asymmetrical Manufacturer OBO Dimension 133x110x2000 Colour Pure white; RAL 9010 Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Туре	GEK-SA133110RW
Manufacturer OBO Dimension 133x110x2000 Colour Pure white; RAL 9010 Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Description 1	Device installation trunking
Dimension 133x110x2000 Colour Pure white; RAL 9010 Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Description 2	asymmetrical
Colour Pure white; RAL 9010 Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Manufacturer	OBO
Material Steel Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Dimension	133x110x2000
Smallest sales unit 2 Unit of quantity Metre Weight 332 kg	Colour	Pure white; RAL 9010
Unit of quantity Metre Weight 332 kg	Material	Steel
Weight 332 kg	Smallest sales unit	2
U U	Unit of quantity	Metre
Weight unit kg/100 m	Weight	332 kg
•	Weight unit	kg/100 m


Technical data sheet

Device installation trunking, desk trunking





Dimensions



Length	2,000 mm
· ·	_,
Width	110 mm
VVIGUI	110111111
Height	133 mm
Height	133 11111
	!

Technical data

Number of covers	1
Number of insertable partitions	1
Rear panel version (inner side)	With locking lugs
Rectangular shape	no
Base perforation	with base perforation
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Usable cross-section	9950 mm²
Cover supplied	no
Cover width	76.5 mm
Protection rating	IP30
Protective film	yes
Protection rating IK code	IK10
Symmetrical	no
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-25 °C