

Technical data sheet

GRAF9-2 service outlet with UT4 45

Item number: 7429608



GRAF9 service outlet for wet-care floors with all necessary system accessories for direct installation in raised floors for indoor use.

The scope of delivery contains:

- GRAF9 service outlet with universal fastening bracket,
- Three UT4/45 universal supports, each for four Modul 45® devices.

Hinged lid with concentric rings. Surface: bare metal with a finely scored structure, recesses painted in the colour RAL 9011, graphite black.

Floor covering protection frame and hinged lid made of die-cast aluminium, tube body made of polyamide.

The minimum installation depth is 75 mm (when using two UT4/45 universal supports) or 110 mm (when using the middle universal support).



AIG Cast aluminium

Master data

Item number	7429608
Type	GRAF9-2 KU 9011
Description 1	Service outlet construct. set
Description 2	for universal mounting
Manufacturer	OBO
Dimension	Ø325X78
Colour	Graphite black; RAL 9011
Material	Cast aluminium
Smallest sales unit	1
Unit of quantity	Piece
Weight	307.5 kg
Weight unit	kg/100 pc.

Technical data

Cable outlet version	Lowerable tube body
Protection rating (IP) when used	IP20
Protection rating (IP) when unused	IP45
Protection rating IK code	IK10
Opening mechanism	Sash lock