Technical data sheet Head plate US 5 FT SOMY

Item number: 7193547





Head plate for mounting on US 5 supports. In combination with the US 5 support, suspended supports of any length can be created in situ. Also suitable for fixing vertical ladders, type SLM 50.

The head plate can be mounted to fixed lengths of the U support, type US 5. The spacer, type DSK 45, is used to install the head plate.

Master data

| Item number | 7193547 |
|---------------------|--------------------------|
| Туре | KUS 5 FT SO |
| Description 1 | Head plate |
| Description 2 | for US 5 support |
| Manufacturer | OBO |
| Dimension | 140x75x104 |
| Material | Steel |
| Surface | Hot-dip galvanised 85 µm |
| Surface standard | DIN EN ISO 1461 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 63 kg |
| Weight unit | kg/100 pc. |

Dimensions

| Length | 140 mm |
|--------|--------|
| Width | 75 mm |
| Height | 104 mm |

Technical data sheet Head plate US 5 FT SOMY

Item number: 7193547



Technical data

| Version for | Screw head plate |
|--------------------------------|------------------|
| Maintain electrical functions | no |
| Suitable for ceiling fastening | yes |
| Suitable for panel fastening | no |
| Suitable for profile shapes | U profile |
| Rustproof steel, pickled | no |
| Angle range, max. | 90 mm |
| Angle range, min. | 90 mm |
| | |