Technical data sheet

Device installation trunking Rapid 80, trunking width 210, trunking height 90 ltem no. 6279600





Device installation trunking without base perforation for direct wall mounting or mounting on panels. Over-lengths up to 6,000 mm for trunking bases and covers as well as other RAL colours can be provided on request. The visible surfaces of the painted device installation trunking are laminated.

The cover must be ordered separately. We recommend the use of the trunking clamp.

Note:

For anodised device installation trunking and fittings made from aluminium, light colour differences caused by tolerance based on the material and process conditions, cannot be avoided (according to DIN 17 611). Alternatively, we recommend powder coating in the colour RAL 9006 (white aluminium).




Alu

Aluminium

Master data

Item no.	6279600	
Туре	GA-D90210RW	
Description 1	Device installation trunking	
Description 2	2 compartments	
Dimension	90x210x2000	
Colour	Pure white	
RAL number	9010	
Material	Aluminium	
Material symbol	Alu	
Smallest sales unit (VG)	2 m	
Weight	378,60 kg/100 m	

Technical data



Length	2.000,00 mm
Width	210,00 mm
Height	90,00 mm
Number of covers	2
Number of insertable partitions	1
Rear panel version (inner side)	Continuous C profile
Rectangular shape	
Base perforation	Without base perforation
Halogen-free	
Cable retaining clip	
Trunking height	90,00 mm
Trunking height	210,00 mm
Duct connector	
Cover mounting type	Internal
Mounting perforation in base	
Usable cross-section	146,88 cm ²
Usable cross-section	14.688,00 mm ²
Cover width	76,5 mm
Cover width 2	76,50 mm
Cover width 3	0,00 mm
Cover supplied	

Technical data sheet

Device installation trunking Rapid 80, trunking width 210, trunking height 90 ltem no. 6279600



Technical data		
Protective 1	film	
Symmetric	al	