## **Technical data sheet**

## Wiring trunking, type LK4 N 80060

**Item number: 6178229** 





Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tapering in the side slots prevents the cables from falling out. Tested to DIN EN 50085-2-3. Special lengths on request.



PVC

Polyvinylchloride

#### Master data


Item number	6178229		
Type	LK4 N 80060		
Description 1	Slotted cable trunking system		
Manufacturer	OBO		
Dimension	80x60x2000		
Colour	Stone grey; RAL 7030		
Material	Polyvinylchloride		
Smallest sales unit	2		
Unit of quantity	Metre		
Weight	82 kg		
Weight unit	kg/100 m		

## **Technical data sheet**

# Wiring trunking, type LK4 N 80060







		ica		

Side wall version	Slotted
Fastening type	Base perforation
Flexible	no
Halogen-free	no
Creepage current-resistant	yes
With cover	yes
Usable cross-section	45.86 cm <sup>2</sup>
Slot spacing	12.5 mm
Slot width	5 mm
Self-extinguishing	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C