


# Technical data sheet

## Cable tray MKS 60 FT SOMY



Item number: 7190109



MKS 60 = Medium-duty cable tray system with a side height of 60 mm.  
Magnetic shield insulation without cover 20 dB, with cover 50 dB.



- St** Steel
- FT SO** Hot-dip galvanised 85 µm

### Master data

Item number	7190109
Type	MKS 640 FT SO
Description 1	Cable tray MKS
Description 2	perforated
Manufacturer	OBO
Dimension	60x400x3000
Material	Steel
Surface	Hot-dip galvanised 85 µm
Surface standard	DIN EN ISO 1461
Smallest sales unit	6
Unit of quantity	Metre
Weight	426.667 kg
Weight unit	kg/100 m


# Technical data sheet

## Cable tray MKS 60 FT SOMY



Item number: 7190109

### Dimensions



Length	3,000 mm
Width	400 mm
Height	60 mm
Plate thickness	1 mm
Dimension B	400 mm

### Technical data

Connector version	Supplied connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	238 cm <sup>2</sup>
Usable cross-section	23800 mm <sup>2</sup>
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

# Technical data sheet


## Cable tray MKS 60 FT SOMY

Item number: 7190109



### Loads

Support spacing 1.5 m	1.5 kN/m
Support spacing 1.75 m	1.25 kN/m
Support spacing 2.0 m	1 kN/m
Support spacing 2.5 m	0.5 kN/m



### Load diagram, cable tray, type MKS 60

- 1** Permitted cable tray/ladder load in kN/m without man load
- 2** Support width in m
- 3** Rail bend in mm at permitted kN/m
- 4** Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width