Technical data sheet

MS4022 mounting rail, heavy duty, slot 18 mm, A2, perforated

Item number: 1121901





Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.



A2

Stainless steel

2B

Bright, treated

Master data

Item number	1121901
Type	MS4022P6000A2
Description 1	Profile rail
Description 2	perforated, slot 18mm
Manufacturer	OBO
Dimension	6000x40x22,5
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	6
Unit of quantity	Metre
Weight	152.5 kg
Weight unit	kg/100 m
· ·	· ·

Technical data sheet

MS4022 mounting rail, heavy duty, slot 18 mm, A2, perforated





13x30 09 009 09 09

ιΣ

22,

Length	6,000 mm
Width	40 mm
Height	22.5 mm
Dimension L	6,000 mm

Technical data

18

2

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	50 mm
Maintain electrical functions	no
Material thickness	2 mm
With perforation	yes
With toothing	no
Profile shape	C profile
Slot width	18 mm
Static value A	1.74 cm ²
Static value ly	1.18 cm
Static value Iz	4.45 cm
Static value Wy	1.05 cm ²
Static value Wz	2.23 cm ²