Technical data sheet

MS4141 mounting rail, slot 22 mm, FS, perforated

Item number: 1122908





Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.



Master data

1122908
MS4141P1000FS
Profile rail
perforated, slot 22mm
OBO
1000x41x41
Steel
Strip galvanized
DIN EN 10346
1
Metre
247.5 kg
kg/100 m

Technical data sheet

MS4141 mounting rail, slot 22 mm, FS, perforated

Item number: 1122908



Dimensions Length Width 1,000 mm 41 mm Height 41 mm Dimension L 1,000 mm <u>14x28</u> 000 50 25 41 S N 4

Technical data

22

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	50 mm
Maintain electrical functions	no
Hole size	14x28 mm
Material thickness	2.5 mm
With perforation	yes
With toothing	yes
Profile shape	C profile
Slot width	22 mm
Static value A	2.97 cm ²
Static value ly	6.05 cm
Static value Iz	9.01 cm
Static value Wy	2.91 cm ²
Static value Wz	4.4 cm ²