

# Technical data sheet

## MS4141PP mounting rail, slot 22 mm, FT, perforated

Item number: 1122501



Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.



**St** Steel

**FT** Hot-dip galvanised

### Master data

Item number	1122501
Type	MS4141PP0400FT
Description 1	Profile rail
Description 2	perforated, slot 22mm
Manufacturer	OBO
Dimension	400x41x41
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	90 kg
Weight unit	kg/100 pc.


# Technical data sheet

MS4141PP mounting rail, slot 22 mm, FT, perforated

Item number: 1122501



## Dimensions



Length	400 mm
Width	41 mm
Height	41 mm
Dimension L	400 mm

## Technical data

Breakable	no
Type of perforation	3 sides perforated
Version for	Single profile
Drill hole spacing, centre	50 mm
Maintain electrical functions	no
Hole size	11x25 mm
Material thickness	2.5 mm
With perforation	yes
With tothing	yes
Profile shape	C profile
Slot width	22 mm
Static value A	2.42 cm <sup>2</sup>
Static value Iy	6 cm
Static value Iz	6.97 cm
Static value Wy	2.49 cm <sup>2</sup>
Static value Wz	2.88 cm <sup>2</sup>