Technical data sheet


MS4141 mounting rail, slot 22 mm, A2, perforated

Item number: 1122982





Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.



Master data

Item number1122982TypeMSL4141P6000A2Description 1Profile railDescription 2perforated, slot 22mmManufacturerOBODimension6000x41x41MaterialStainless steelSurfaceBright, treatedSurface standard6Unit of quantityMetreWeight201.1 kg		
Description 1Profile railDescription 2perforated, slot 22mmManufacturerOBODimension6000x41x41MaterialStainless steelSurfaceBright, treatedSurface standard6Unit of quantityMetreWeight201.1 kg	Item number	1122982
Description 2perforated, slot 22mmManufacturerOBODimension6000x41x41MaterialStainless steelSurfaceBright, treatedSurface standard6Smallest sales unit6Unit of quantityMetreWeight201.1 kg	Туре	MSL4141P6000A2
ManufacturerOBODimension6000x41x41MaterialStainless steelSurfaceBright, treatedSurface standard6Unit of quantityMetreWeight201.1 kg	Description 1	Profile rail
Dimension6000x41x41MaterialStainless steelSurfaceBright, treatedSurface standard6Smallest sales unit6Unit of quantityMetreWeight201.1 kg	Description 2	perforated, slot 22mm
Material Stainless steel Surface Bright, treated Surface standard 6 Unit of quantity Metre Weight 201.1 kg	Manufacturer	OBO
Surface Bright, treated Surface standard Bright, treated Smallest sales unit 6 Unit of quantity Metre Weight 201.1 kg	Dimension	6000x41x41
Surface standard6Smallest sales unit6Unit of quantityMetreWeight201.1 kg	Material	Stainless steel
Smallest sales unit 6 Unit of quantity Metre Weight 201.1 kg	Surface	Bright, treated
Unit of quantity Metre Weight 201.1 kg	Surface standard	
Weight 201.1 kg	Smallest sales unit	6
5	Unit of quantity	Metre
	Weight	201.1 kg
vveight unit kg/100 m	Weight unit	kg/100 m

Technical data sheet

MS4141 mounting rail, slot 22 mm, A2, perforated

Item number: 1122982



Dimensions Length Width 6,000 mm 41 mm Height 41 mm Dimension L 6,000 mm 14x28 6000 50 25 ۱ 41 N

Technical data

4

22

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	50 mm
Maintain electrical functions	no
Hole size	14x28 mm
Material thickness	2 mm
With perforation	yes
With toothing	yes
Profile shape	C profile
Slot width	22 mm
Static value A	2.45 cm ²
Static value ly	5.18 cm
Static value Iz	7.56 cm
Static value Wy	2.51 cm ²
Static value Wz	2.69 cm ²