
# **Technical data sheet**

Extension unit for GESR9, height 40-140 mm

## Item number: 7424326





Ready for mounting trunking extension unit with a device installation lid for the in-stallation of a flush-mount unit of nominal size R9, consisting of side profiles with attached flexible side wall made of metal mesh, floor covering contact profiles, trunking lid with blank, closed mounting opening and a trunking end piece. The scope of delivery contains 3 height-adjustable fixing brackets, 3 screed anchors, 1 lid butt support (without levelling unit – please order separately) and 1 con-struction set for 90° angle. Size of the mounting unit suitable for the installation of a round installation unit of


nominal size R9 or R9/55.



Strip galvanized FS

#### Master data

Item number	7424326
Туре	OKA-G A 40140R9
Description 1	Extension unit
Description 2	for service unit GESR9
Manufacturer	OBO
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	666 kg
Weight unit	kg/100 pc.



Length	460 mm
Width	400 mm
Dimension A	400 mm
Dimension d Ø	305 mm
Dimension h	40 mm

## **Technical data sheet**

Extension unit for GESR9, height 40-140 mm

### Item number: 7424326

**Technical data** 



#### Mounting opening cover yes Covers 1 Number of mounting openings 1 Floor plate no Cover fastening, locking no Seal installation option yes Installation opening for on-floor no tank Installation opening for flush-mount unit Round Decouplable ves Suitable for expansion joint no Suitable for screed-flush closed underfloor ducts no Suitable for flushfloor, open unyes derfloor trunking Suitable for screed-covered unno derfloor ducts Trunking height, max. 140 mm Duct height, min. 40 mm Cover material thickness 4 Minimum screed height 40 With connection opening yes With separating retainer no With overhang yes Mounting opening For service outlet Nominal size for device installati-R9 on units Height-adjustment range, max. 140 mm Height-adjustment range, min. 40 mm Removable cover yes