Technical data sheet

Cover clip for WDKH trunking, trunking width 150 mm

Item number: 6176131

Cover clip for better and easier laying of lines in the WDKH trunking. The cover fixing device can be moved along the entire length of the trunking. The cover clip is locked on one side and moved forward. This provides a 30° opening, meaning that cable routing is very simple.







Polycarbonate/AcryInitrile-butadiene-styrene

Master data

| Item number | 6176131 |
|---------------------|----------------------------------------------|
| Туре | OTK H150 |
| Description 1 | Cover fixing device |
| Description 2 | halogen-free |
| Manufacturer | OBO |
| Dimension | 116x29 |
| Colour | Pure white; RAL 9010 |
| Material | Polycarbonate/AcryInitrile-butadiene-styrene |
| Smallest sales unit | 10 |
| Unit of quantity | Piece |
| Weight | 2.05 kg |
| Weight unit | kg/100 pc. |

Dimensions

| | - | | а | - |
|---|----|---|----|---|
| t | | | 20 | |
| ٩ | ļ. | 0 | 0 | |

| Length | 36 mm |
|-------------|----------|
| Width | 136.2 mm |
| Height | 10.5 mm |
| Dimension a | 136.2 mm |
| Dimension b | 36 mm |

Technical data sheet

Cover clip for WDKH trunking, trunking width 150 mm

Item number: 6176131



Technical data

| Fastening type | Lockable |
|-----------------------------------|----------|
| Maintain electrical functions | no |
| Halogen-free | yes |
| With equipotential bonding | no |
| Cover width | 150 mm |
| Protection rating | IP30 |
| Protection rating IK code | IK07. |
| Self-extinguishing | yes |
| Permitted temperature range, max. | 90 °C |
| Permitted temperature range, min. | -5 °C |