## **Technical data sheet**

Wall connection collar, 3- and 4-sided, duct height 80 mm, pure white

**Item number: 7218128** 





Wall connection collar, 4-sided, with integrated seal for PYROLINE® Rapid PLM installation duct. For mounting in the area of wall and ceiling connections as well as wall penetrations. Can also be used as 3-sided wall connection collar for direct wall or ceiling mounting of the duct.

CE

St

Steel

P

Powder-coated

## Master data

Item number	7218128
Туре	PLM WC 0810 RW
Description 1	Wall connection collar
Description 2	3- and 4-sided
Manufacturer	OBO
Dimension	85x253x233
Colour	Pure white; RAL 9010
Material	Steel
Surface	Powder-coated
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	64.3 kg
Weight unit	kg/100 pc.


## **Technical data sheet**

Wall connection collar, 3- and 4-sided, duct height 80 mm, pure white





Dimensions				
	<b>∮</b>	Dimension B	252 mm	
	rÕ	Dimension b	100 mm	
	- ∞	Dimension D	232 mm	
		Dimension d	80 mm	
252				



**Technical data** 

Type of accessory	Wall connection collar
Accessories	yes
Spare part	no