# **Technical data sheet**

#### 45° bend 60 FS

**Item number: 6036108** 



45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.



# CER

St

Steel

FS

Strip galvanized

#### Master data

Item number 6036108 Type RB 45 640 FS Description 1 45° bend Description 2 for cable tray, horizontal Manufacturer OBO Dimension 60x400 Material Steel		
Description 1 45° bend Description 2 for cable tray, horizontal Manufacturer OBO Dimension 60x400	Item number	6036108
Description 2 for cable tray, horizontal  Manufacturer OBO  Dimension 60x400	Туре	RB 45 640 FS
Manufacturer OBO Dimension 60x400	Description 1	45° bend
Dimension 60x400	Description 2	for cable tray, horizontal
	Manufacturer	OBO
Material Steel	Dimension	60x400
	Material	Steel
Surface Strip galvanized	Surface	Strip galvanized
Surface standard DIN EN 10346	Surface standard	DIN EN 10346
Smallest sales unit 1	Smallest sales unit	1
Unit of quantity Piece	Unit of quantity	Piece
Weight 158.7 kg	Weight	158.7 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

## **Technical data sheet**

### 45° bend 60 FS

**Item number: 6036108** 



# 

396 479

Width	400 mm
Height	60 mm
Plate thickness	1 mm
Dimension B	400 mm

#### Technical data

Bend (angle)	45°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	yes
Material thickness, floor plate	1 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	14 St.
Rail thickness	1.25 mm