## Technical data sheet Cross-over 60/100 A4

### Item number: 7027520



Cross-over for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.





2B Bright, treated


#### Master data

Item number	7027520
Туре	RK 610 A4
Description 1	Cross over
Description 2	for cable tray
Manufacturer	OBO
Dimension	60x100
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	88.4 kg
Weight unit	kg/100 pc.

# Technical data sheet Cross-over 60/100 A4

### Item number: 7027520





Width	100 mm
Height	60 mm
Plate thickness	0.8 mm
Dimension B	100 mm

**Technical data** 

Connector versionIntegrated connectorMaintain electrical functionsyesMaterial thickness, floor plate0.8 mmNATO hole patternnoRustproof steel, picklednoPermitted temperature range, max.120 °CPermitted temperature range, min20 °CWide-span versionnoType of connector, cable support systemScrewed		
Material thickness, floor plate   0.8 mm     NATO hole pattern   no     Rustproof steel, pickled   no     Permitted temperature range, max.   120 °C     Permitted temperature range, min.   -20 °C     Wide-span version   no     Type of connector, cable support   Screwed	Connector version	Integrated connector
NATO hole patternnoRustproof steel, picklednoPermitted temperature range, max.120 °CPermitted temperature range, min20 °CWide-span versionnoType of connector, cable supportScrewed	Maintain electrical functions	yes
Rustproof steel, pickled   no     Permitted temperature range, max.   120 °C     Permitted temperature range, min.   -20 °C     Wide-span version   no     Type of connector, cable support   Screwed	Material thickness, floor plate	0.8 mm
Permitted temperature range, max.   120 °C     Permitted temperature range, min.   -20 °C     Wide-span version   no     Type of connector, cable support   Screwed	NATO hole pattern	no
max. Permitted temperature range, min. -20 °C   Wide-span version no   Type of connector, cable support Screwed	Rustproof steel, pickled	no
min. Wide-span version no   Type of connector, cable support Screwed	1 0 /	120 °C
Type of connector, cable support Screwed		-20 °C
	Wide-span version	no
		Screwed
Recommended quantity of bolts 20 St.	Recommended quantity of bolts	20 St.
Rail thickness 1.25 mm	Rail thickness	1.25 mm