

Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height 58 mm

Item number: 7400271



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking lid. With separating retainer in the trunking base. Only compatible with the UZD250-4/350-4.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St Steel

FS Strip galvanized

Master data

Item number	7400271
Type	S2 25058-2
Description 1	Underfloor duct, 2-part
Description 2	2 compartments
Manufacturer	OBO
Dimension	2000x250x58
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	433.453 kg
Weight unit	kg/100 m

Dimensions

Length	2,000 mm
Width	250 mm
Height	58 mm
Dimension a	110 mm
Dimension b	140 mm
Dimension h	58 mm

Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height
58 mm

Item number: 7400271



Technical data

Number of fixed partitions	1
Number of compartments	2 St.
Floor plate	yes
Application area	Scree-covered
Decouplable	no
Trunking width, min.	250 mm
Duct height, min.	58 mm
Usable cross-section	13300 mm ²
Removable cover	yes
Cross-section, draw a	5800 mm ²
Cross-section, draw b	7500 mm ²