Technical data sheet

AR45 socket unit, double, with labelling panel for horizontal device installation **Item number: 6119427**





Pre-terminated socket unit with labelling panel, suitable for installation in Rapid 80 device installation trunking systems.

Socket unit, consisting of:

- Accessory mounting box, double, type 71GD13
 Protective contact socket, double, 0° connection direction, colour: see table
 Cover frame AR45, double, with labelling panel, type AR45-BF.., colour: pure

For installation in Rapid 80 device installation trunking and ISS service poles.

Polycarbonate

Master data


Item number	6119427
Туре	SDE-RW D0RW2B
Description 1	Socket unit
Description 2	for double Modul 45
Manufacturer	OBO
Dimension	84x140x59mm
Colour	Pure white; RAL 9010
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	19 kg
Weight unit	kg/100 pc.

Technical data sheet

AR45 socket unit, double, with labelling panel for horizontal device installation ltem number: 6119427



Dimensions Width 140 mm Height 84 mm



Technical data

Cover	Complete housing
Closable	no
Connection type	Screwless terminal
Number of units	2
Number of modules (for modular construction)	0
Number of switchable sockets	0
Number of poles	2
Printed label/coding	Without printing
Version for	Double 0°
Surface version	Matt
Version for	SCHUKO
Ejection mechanism	no
Fastening type	Lock
Labelling panel	yes
increased touch protection	yes
Error current protection	no
For more difficult conditions (according to VDE)	no
Power reserve	no
Halogen-free	yes
Insulated installation	no
Hinged cover	no
Coding	no
Warning light	no
With on/off switch	no
With fine-wire fuse	no
With functional lighting	no
With orientation lighting	no
Mounting type	Device installation duct
Nominal voltage	250 V
Nominal current	16 A
Protection rating	Other

Technical data sheet

AR45 socket unit, double, with labelling panel for horizontal device installation ltem number: 6119427



Technical data		
	Special power supply	Without special power supply
	Socket version	Protective contact
	Socket angle	0°
	Depth	60 mm
	Transparent	no
	Rotated central insert	no
	Surge protection	no