

Technical data sheet

UDHOME9 floor box, freely equippable, stainless steel

Item no. 7427324



Square floor box for use in dry-cleaned cavity and screed floors for indoor use. Installation housing with pre-marked insertion openings for pipelines (M25). Cover adjustable to the top edge of the floor covering using four height-adjustment supports. The minimum installation depth is 95 mm, the height-adjustment range + 30 mm.

Surfaces visible in the floor covering made of stainless steel.





VA Stainless steel, rustproof 1.4301

Master data

Item no.	7427324
Type	UDHOME9 2V
Description 1	Floor box, complete
Description 2	empty
Material	Stainless steel, material no. 1.4301
Material symbol	A2
Smallest sales unit (VG)	1 Piece
Weight	470,00 kg/100 pc.

Technical data



Length	244,00 mm
Width	244,00 mm
Dimension h	95,00 mm
Wide external dimensions	244,00 mm
Wide installation dimensions	250,00 mm
Length of external dimensions	244,00 mm
Length of installation dimensions	250,00 mm
Cable outlet version	Swivellable cord outlet
Floor covering thickness	15,00 mm
Screed height	95-110 mm
Floor height	95-125 mm
Suitable for wet care	<input type="checkbox"/>
Suitable for screed-flush closed underfloor ducts	<input type="checkbox"/>
Suitable for screed-covered underfloor ducts	<input type="checkbox"/>
Suitable for raised floor installation	<input checked="" type="checkbox"/>
Suitable for cavity floor installation	<input checked="" type="checkbox"/>
Suitable for underfloor ducts	<input type="checkbox"/>
With floor covering recess	<input checked="" type="checkbox"/>
Height-adjustment range	95,00 - 125,00 mm
Opening mechanism	Handle