

Technical data sheet

Concealed accessory/connection box



Item number: 2003023



Device/connection socket with increased socket volume on both sides of the device installation opening to accept connection terminals. Torsion-resistant guaranteed standard combination spacing of 71 mm (to DIN 49 073-1) through snap-lock coupling. Break-out openings for cables and pipes of up to \varnothing 21 mm, low-lying plaster brackets, device bolt spacing 60 mm, for screw fastening with 3.2 mm self-tapping screws, with 4 screw bosses and 2 device screws, protection rating IP20.



PS Polystyrene

Master data

Item number	2003023
Type	UG 60 VK
Description 1	Device/connection box
Description 2	concealed
Manufacturer	OBO
Dimension	70x110x48
Colour	Black
Material	Polystyrene
Smallest sales unit	10
Unit of quantity	Piece
Weight	4.6 kg
Weight unit	kg/100 pc.

Technical data sheet


Concealed accessory/connection box



Item number: 2003023

Dimensions

Length	110 mm
Width	70 mm
Height	48 mm



Technical data

No. of entries	8
Number of switch boxes	1
Type of insertion...	break-out openings for cables and pipes to Ø 21 mm
Type of housing penetration	Pre-marking
Version for	Single
Type	Device connection socket/box
Device fixing	Screws ,
Equipment	Without
Cover	Without
Cover fastening	Not applicable
Entry from rear	no
Entries	8
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Rectangular
Maintain electrical functions	Without
Floor height, min.	50 mm
for pipe diameter	20 mm
Accessory screw clearance	60 mm
Halogen-free	yes
With screening	no
With nail strap	no
With bolts	yes
Mounting type	Concealed
Nominal cross-section, max.	2.5 mm ²
Nominal cross-section, min.	1.5 mm ²
Sealable	no
Impact-resistant	yes
Protection rating	IP20
Support	Tunnel support
Airtight	no
Rated voltage	400 V